

GENERAL[®]

Video Inspection Systems

THE SEEKER™ 300 SERIES

Compact video camerascopes for the visual inspection of inaccessible areas

Applications:

Ideal for inspection of hard-to-reach or hard-to-see areas or equipment. Many potential applications in the automotive repair, plumbing, construction, restoration and HVAC/R industries

System Descriptions:

There are two SEEKER 300 Series systems available:

- 1) **The DCS300 System** with a 12mm (0.47 in.) diameter x 1m (3.28 ft.) long flexible-obedient far-focus camera-tipped probe
- 2) **The DCS355 System** with a 5.5mm (0.22 in.) diameter x 1m (3.28 ft.) long flexible-obedient close-focus camera-tipped probe

Features:

- View inspection video instantly on the 3.5 in. (88.9mm) color LCD screen
- Separate monitor buttons for 2x zoom and 180° image flip
- Camera-tipped probes have built-in adjustable LED lighting
- Probes are flexible, strong and slim enough to perform automotive engine check-up
- Interchangeable probes are water, oil and dust proof to IP67 standards
- Probes are flexible-obedient and will retain configured shape to suit various inspection needs

Specifications:

BASE SYSTEM WITH MONITOR:

Display: 3.5 in. (88.9mm) Color LCD
Resolution: 320 x 240 pixels
Operating Temperature: 32° to 113°F (0° to 45°C)
Power Source: 1 "9V" battery (included)
Weight: 16 oz. (454g)

SYSTEM PROBES:

All probes are:

- Camera-tipped with built-in adjustable LED lighting
- Flexible, strong and slim enough to perform automotive engine check-up
- Water, oil and dust proof to IP67 standards
- Flexible-obedient and will retain configured shape to suit various inspection needs

GENERAL[®]

General Tools & Instruments

80 White Street, New York, NY 10013-3567
 TEL: 212. 431. 6100 TOLL FREE: 800. 697. 8665
 sales@generaltools.com www.generaltools.com
 DCS300SS Printed in USA



CE

No. DCS300



Includes:

Custom Hard Case, Pistol Grip Camera Handle with 1m Long, Flexible-Obedient Probe, 3 Accessory Tools, 1 "9V" Battery, Mini Screwdriver, User's Manual, 3 Year Limited Warranty

Specifications: (continued)

DCS300

Supplied Probe: 12mm (See System Descriptions)
Light Source: 2 adjustable high-intensity LEDs
Field of View: 60°
Tip Accessories: 45° Mirror, Magnetic Pick-Up, Pick-Up Hook
Optional 12mm Dia. Probe Extensions:
 1m, 2m, 3m (3.28 ft., 6.6 ft., 9.9 ft.)
 for maximum extension of 5m (16 ft.)

Optional Probes:

- 1) The 12mm close-focus probe
- 2) The 5.5mm close-focus probes
- 3) The 9mm close-focus probes

DCS355

Supplied Probe: 5.5mm (See System Descriptions)
Light Source: 4 Adjustable High Intensity LEDs
Field of View: 60°
Tip Accessories: Thread protector, ball guide and mirror

Optional Probes:

- 1) Other 5.5mm close-focus probes
- 2) The 9mm close-focus probes
- 3) The 12mm close-focus probe
- 4) The 12mm far-focus probe
- 5) The 12mm probe extensions

