

GENERAL®

Pinless LCD Moisture Meter

Ideal for measuring moisture content of wood and other construction materials

Features:

- Non-invasive measurement technology
- Jumbo display
- Wide measurement range
- Intuitive on-screen icons: Low/Medium/High moisture content; wood/concrete mode
- Hold function
- Audible peak reading alert
- Auto-calibrating
- Auto power Off

Specifications:

Ranges:

0 to 99.9% WME (Wood Moisture Equivalent) for wood; 0 to 56.5% for building materials

Accuracy/Resolution: $\pm 3\%/0.1\%$

Measuring Depth: 3/4 in. (20mm)

Auto Power Off Trigger:

3 to 4 minutes with 0% reading

Low/Very Low Battery Warning Triggers:

<7.5V/<6.5V

Operating Temperature:

32° to 122°F (0° to 50°C)

Operating Relative Humidity: <80%

Dimensions:

6.6 x 3.0 x 2.7 in.
(170 x 77 x 40mm)

Weight: 10.4 oz. (255g)

Power Source: 1 "9V" battery (included)

Prevent Mold!



No. MMD5NP



Teak planks become bendable and stable with 15% moisture



Locate moisture/water damage

GENERAL®

General Tools & Instruments

80 White Street, New York, NY 10013-3567

TEL: 212. 431. 6100 TOLL FREE: 800. 697. 8665

sales@generaltools.com www.generaltools.com

MMD5NPSS Printed in USA 05/13